



ASPHALT HOTBOX



HMT8000ODL Model Shown

AVAILABLE SIZES

4,000 gal

8,000 gal

Marathon's premium asphalt hot boxes are heavy duty, fully insulated and customizable to suit your needs! This particular model is diesel fired and equipped with an oil jacketed material vat to keep your asphalt warmer for longer periods of time when traveling between job sites. The hydraulic scissor hoist creates superior stability when unloading asphalt and decreases operator fatigue to keep your crews working! These units are ideal for cities, municipalities, as well as contractors both big and small!

FEATURES

- Polyhedral material vat featuring a 10° rear-sloped floor with all other walls channeling material directly towards rear gate.
- Electrically actuator top loading doors to decrease operator fatigue.
- Outfitted with a stainless steel front, rear wall, shovelling platform and top loading doors to protect against exposure to harsh weather and resist damage from tools and asphalt build-up.
- Versatile tandem axle trailer design with a low center of gravity giving the unit more stability.
- An 8 gallon tool rinse tank, 4 pc tool rack, 3 gallon release agent spray bottle come standard on all models.

SPECIFICATIONS

Model	HMT8000ODL
Shipping Weight	
Shipping Weight	6,669 lbs (3,025 kg)
Capacity	
Hot Mix Chamber	8,000 lbs (3,629 kg)
Heat Transfer Oil	67.5 gal (255.5 L)
Dimensions	
Overall Length	236"
Overall Width	80.5"
Overall Height	88"
Overall Height with Arrow Bar	103"
Overall Height with Door Up	127"
Hopper Opening (L x W)	83" L x 62" W
Rear Unloading Door	11" H x 18" W
Shoveling Platform	
Height from Ground	26"
Diesel Burner	165,000 BTU
Hopper Insulation	1" ceramic body with 2" fibreglass lid
Suspension	
Axle(s)	Tandem
Load Capacity	16,000 lbs (7,257 kg)
Tires	(4) 235/85/R16

***Specifications subject to change without notice**

OIL-JACKETED FEATURES

Our equipment has a reputation for outlasting the competition! Oil jacketed units have a longer lifespan in comparison to air jacketed versions as the oil absorbs the heat generated by the burner and the flame no longer acts as the heat source for the asphalt, saving the lifespan of the steel.

Oil jacketed units produce even heat distribution throughout the whole hopper so that asphalt doesn't burn or soften unevenly throughout. Our design has superior heat retention and comes standard with automatic temperature control to consistently maintain the quality of your product and eliminate the need for frequent burner on/off control.

Oil jacketed models feature a 120V overnight heater to keep asphalt warm overnight to minimize heat up time the next day.

HYDRAULIC DUMP FEATURES

42° hydraulic dumping angle plus the 10° provided by the floor guarantees maximum material output. Dual safety lock-out bars will support vat at 20° for maintenance. Hydraulic scissor hoist for superior stability when dumping asphalt.

Fully enclosed hydraulic powerpack with a single magnetic & detachable operator pendant to allow hopper control from desired location.

Alarm sounds whenever tilt system is operated downwards for operator safety.

OPTIONS

- 300,000 BTU hand held vapor propane torch with 15' hose
- 30 gallon insulated tack tank (available in propane or diesel heating)
- Power spray system with engine, pump, spray wand, flushing tank and hose reel
- Compactor plate with hoist & electric winch
- LED work lights
- Tool box installed
- Hydraulic surge brakes
- Spare tire & rim mounted
- 2-5/16" ball hitch