


# UNDER FIRED HOT TACK KETTLES



KEB260DT Model Shown

## AVAILABLE SIZES

260 gal

500 gal

Marathon's under fired hot tack sprayers provide a fast and reliable means of heating and applying solvent based emulsions, tack coats and asphalt cement. Our units are capable of heating a large volume of material on a steady basis and offer many operator friendly features and options.

## FEATURES

- Manufactured with 10 GA steel for a long service life.
- 1" Ceramic blanket insulation added to retain heat.
- Units come equipped with a large 18" x 26" reverse-load, anti-splash lid for operator safety.
- Electric brakes and breakaway kits come standard on all trailer mounted equipment.
- Low profile for safe and easy loading and towing.

## SPECIFICATIONS

Models	KEB260DT	KEB500DT
Shipping Weight	2,839 lbs (1,288 kg)	4,123 lbs (1,870 kg)
Burner	(1) 340,000 BTU diesel fired	(1) 340,000 BTU diesel fired
Material Capacity	260 gal (983 L)	500 gal (1,892 L)
<b>Dimensions</b>		
Overall Length	192"	224"
Overall Width	78"	90"
Overall Height	68"	66"
Loading Height	52"	52"
<b>Suspension</b>		
Axle(s)	Single	Tandem
Load Capacity	5,200 lbs (2,363 kg)	10,400 lbs (4,718 kg)
Tires - Size	(2) 205/75/R15	(2) 225/75/R15

**\*Specifications subject to change without notice**

## OPTIONS

- Power spray system with engine, pumping system, spraywand, flushing tank and recovery tank
- Hydraulic surge brakes
- Amber strobe light
- Flashing LED arrow stick advisor
- Spare tire and rim (mounted)