

UNDER FIRED HOT TACK KETTLES



KEB500PT Model Shown

AVAILABLE SIZES

115 gal

260 gal

500 gal

Marathon's under fired hot tack sprayers provide a fast and reliable means of heating and applying solvent based emulsions, tack coats and asphalt cement. Our units are capable of heating a large volume of material on a steady basis and offer many operator friendly features and options.

FEATURES

- Manufactured with 10 GA steel for a long service life.
- 1" Ceramic blanket insulation added to retain heat.
- Units come equipped with a large 18" x 26" reverse-load, anti-splash lid for operator safety.
- Electric brakes and breakaway kits come standard on all trailer mounted equipment.
- Low profile for safe and easy loading and towing.

SPECIFICATIONS

Models	KEB115PT	KEB260PT	KEB500PT
Shipping Weight	1,315 lbs (596 kg)	2,839 lbs (1,288 kg)	3,589 lbs (1,627 kg)
Burners	(1) 410,000 BTU vapour propane	(1) 410,000 BTU vapour propane	(1) 410,000 BTU vapour propane
Material Capacity	115 gal (435 L)	260 gal (983 L)	500 gal (1,892 L)
Dimensions			
Overall Length	158"	192"	224"
Overall Width	54"	80"	90"
Overall Height	68"	70"	70"
Loading Height	52"	52"	52"
Suspension			
Axle(s)	Single	Single	Tandem
Load Capacity	3,500 lbs (1,591 kg)	5,200 lbs (2,363 kg)	10,400 lbs (4,718 kg)
Tires - Size	(2) 205/75/R15	(2) 225/75/R15	(4) 225/75/R15

***Specifications subject to change without notice**

OPTIONS

- Power spray system with engine, pumping system, spraywand, flushing tank and recovery tank
- Digital automatic temperature control system
- Hydraulic surge brakes
- Amber strobe light
- Flashing LED arrow stick advisor
- Spare tire and rim (mounted)