

TUBE FIRED HOT TACK SPRAYERS



TPS115PS Model Shown

AVAILABLE SIZES

115 gal

250 gal

500 gal

Marathon's hot tack sprayers provide a fast and reliable means of heating and applying bituminous emulsions and tack coats. Our units are capable of heating a large volume of bitumen on a steady basis and offer many operator friendly features and options.

FEATURES

- Manufactured with 10 GA steel for a long service life.
- Standard models come with a 5hp engine and a 10 GPM pumping system.
- Electric brakes and breakaway kits come standard on all trailer mounted equipment.
- 10" diameter vented flip-top filler lid for fast material filling.
- A 5' spray wand and 50' material hose comes mounted on a heavy duty hose reel.
- Units are equipped with a large 10 gallon flushing tank 12 gallon recovery tank and a 2" material dispensing valve.

SPECIFICATIONS

| Models | TPS115PS | TPS250PT | TPS500PT |
|-----------------|-------------------------------|-------------------------------|-------------------------------|
| Shipping Weight | 619 lbs (280 kg) | 1,407 lbs (638 kg) | 2,723 lbs (1,235 kg) |
| Engine | 5 HP | 5 HP | 5 HP |
| Tank Capacity | 115 gal (435 L) | 250 gal (946 L) | 500 gal (1,892 L) |
| Pump | 10 GPM | 10 GPM | 10 GPM |
| Burner | (1) 80,000 BTU vapour propane | (2) 80,000 BTU vapour propane | (2) 80,000 BTU vapour propane |

Dimensions

| | | | |
|----------------|-----|------|------|
| Overall Length | 44" | 134" | 166" |
| Overall Width | 56" | 72" | 80" |
| Overall Height | 45" | 68" | 74" |
| Loading Height | 25" | 47" | 54" |

Suspension

| | | | |
|---------------|-----|----------------------|--------------------------|
| Axle(s) | N/A | Single | Tandem |
| Load Capacity | N/A | 5,200 lbs (2,359 kg) | (2) 5,200 lbs (4,718 kg) |
| Tires - Size | N/A | (2) 225/75/R15 | (4) 225/75/R15 |

***Specifications subject to change without notice**